

AnchorMark

Premium Concrete Screw AM Premium Threaded Rod Hanger

High end, powerful screw solution for fast and simple installation.



LEARN MORE



AnchorMark

Premium Construction Fasteners

AM Premium Threaded Rod Hanger

TECHNICAL DATA



Rod Hanger Head (6 x 40 mm)



Rod Hanger Head (8 x 60 mm)

AnchorMark - Premium Threaded Rod Hanger

*Refer to ETA 15/0905 on our website for more information



Type [Zinc Plated Steel]	Art. No.	Head- type	Coupler remov- able	ETA full range approved	SEISMIC C1 approved	SEISMIC C2 approved	Drill [mm]	Ø Drill hole in object [mm]	Ø Screw [mm]	Thread length [mm]	Min. drill depth at push through hole [mm]	Min. screw in depth [mm]	Max. useable length [mm]	Internal Thread Size	Instal- lation torque [Nm]	Acti- vation	Oty. per inner box [pcs]
6 x 40 mm	519100	HEX	YES	■	■	■	6	8-9	7,5	40	50	40	0	M8 + M10	15	SW 13	50
8 x 60 mm	519105		NO	■	■	■	8	11-12	10,5	60	70	60	0	M 10	25		100

* recommended loads are for single anchors in C20/25 uncracked concrete load tested far away from other anchors and from edges.



Also available: Truss Head



CSK Head



HEX Head

FUNCTIONING

- The AM rod hanger concrete screw is suitable for push-through installation.
- When the rod hanger screw is screwed into the drill hole, the thread flanks cut positively into the concrete.
- Use a torque wrench for easy installation.
- Do not exceed the maximum installation torque.
- Easy and quick installation.

ADVANTAGES

- Removable rod coupler (*exclusive for the 6x40mm*)
- Simple and time-saving threaded screws for the use in concrete.
- Completely removable anchor suitable for temporary fixings.
- Virtually expansion-free operation allows cost-efficient fixing with small axial spaces and edge distances
- Made of zinc-plated steel, high load capacity.
- The ETA covers applications in cracked and non-cracked concrete and seismic performance categories C1 and C2 (see ETA for more detail).

BUILDING MATERIALS

- Concrete C20/25 to C50/60, cracked and non-cracked
- Prestressed hollow core concrete slabs, strength C30/37



info@anchormark.com.au



+61 3 9799 2096



anchormark.com.au