

Nylon toggle DuoTec

Recommended loads¹⁾²⁾ for a single anchor.

Type		DuoTec 10				DuoTec 12				
		Chipboard screws		Metrical screw	fischer Hook	Chipboard screws		Metrical screw	fischer Hook	
Screw diameter	[mm]	4.5	5.0	5.0	5.0	5.0	6.0	6.0	5.5	
Recommended loads in the respective base material $F_{rec}^{3)}$ for a span in the construction $b = 625$ mm										
Gypsum plasterboard	9.5 mm	[kN]	0.17	0.17	0.17	0.17	0.17	0.17	0.17	
Gypsum plasterboard	12.5 mm	[kN]	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Gypsum plasterboard	2 x 12.5 mm	[kN]	0.43	0.43	0.43	0.30 ⁴⁾	0.43	0.43	0.43	
Gypsum fibreboard	12.5 mm	[kN]	0.51	0.51	0.51	0.30 ⁴⁾	0.51	0.51	0.50 ⁴⁾	
Chipboard	16 mm	[kN]	0.71	0.71	0.71	0.30 ⁴⁾	0.75	0.80	0.50 ⁴⁾	
OSB board	18 mm	[kN]	0.75	0.75	0.75	0.30 ⁴⁾	0.75	1.30	0.50 ⁴⁾	
Recommended loads in the respective base material $F_{rec}^{3)}$ for a span in the construction $b = 120$ mm										
Gypsum plasterboard	9.5 mm	[kN]	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Gypsum plasterboard	12.5 mm	[kN]	0.36	0.36	0.36	0.30 ⁴⁾	0.36	0.36	0.20	
Gypsum plasterboard	2 x 12.5 mm	[kN]	0.59	0.59	0.59	0.30 ⁴⁾	0.70	0.80	0.50 ⁴⁾	
Gypsum fibreboard	12.5 mm	[kN]	0.75	0.75	0.75	0.30 ⁴⁾	0.80	1.10	0.50 ⁴⁾	
Chipboard	16 mm	[kN]	0.75	0.75	0.75	0.30 ⁴⁾	0.80	1.40	0.50 ⁴⁾	
OSB board	18 mm	[kN]	0.75	0.75	0.75	0.30 ⁴⁾	0.80	1.50	0.50 ⁴⁾	
Recommended loads in solid building materials $F_{rec}^{3)}$										
Concrete	\geq C20/25	[kN]	0.45	0.75	-	0.30 ⁴⁾	0.40	0.75	-	0.30
Wood		[kN]	0.30	0.75	-	0.30 ⁴⁾	0.20	0.65	-	0.30
Recommended loads in the respective base material $F_{rec}^{3)}$										
Hollow block of lightweight aggregate concrete „Sepa Parpaing“	$f_b \geq 8$ N/mm ²	[kN]	-	-	-	-	0.65	1.00	1.00	0.50 ⁴⁾
Pre-stressed hollow-core concrete slabs		[kN]	-	-	-	-	1.00	1.40	1.30	0.50 ⁴⁾
Lightweight concrete hollow block Hbl acc. to EN 771-3	$f_b \geq 2$ N/mm ²	[kN]	-	-	-	-	0.90	1.00	1.00	0.50 ⁴⁾

¹⁾ Required safety factors are considered.

²⁾ The recommended loads are reference values and depending to the building material and the workmanship. The values are only valid for the given screw diameter.

³⁾ Valid for tensile load, shear load and oblique load under any angle.

⁴⁾ Bending of the hook is decisive. Only for tension load.