

## Tradegear Ltd

Telephone: 0800 22 44 34

24hr Emergency Ph: +64 21 510 624

Fax: 0800 22 11 51

Email: [office@tradegear.co.nz](mailto:office@tradegear.co.nz)

Web: [www.tradegear.co.nz](http://www.tradegear.co.nz)

## Tradegear Marking Spray



**Tradegear Marking Spray** is a premium marking out paint designed for a range of applications including; construction, landscaping, civil works and surveying.

Tradegear Marking Spray is suitable for use with the Long Arm Handle and 2 Wheel Spot Marking Handle, also available from Tradegear.

## DIRECTIONS FOR USE

### Suitable Surfaces

Concrete, bitumen, steel and timber.

### Ideal Application Temperature

Between -10°C and 40°C. Avoid use in windy conditions.

### Before use

Refer to Technical Data Sheet and Safety Data Sheet before use.

### Application

Before spraying, **Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can in the **INVERTED** position (**upside down**), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

### Drying Time

Touch dry in 5 minutes (25°C).

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

### After Spraying

**Prevent blocking** by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with **Acetone or General Purpose Thinner**.

## Tradegear Ltd

Telephone: 0800 22 44 34

24hr Emergency Ph: +64 21 510 624

Fax: 0800 22 11 51

Email: [office@tradegear.co.nz](mailto:office@tradegear.co.nz)

Web: [www.tradegear.co.nz](http://www.tradegear.co.nz)

## TECHNICAL DATA

<b>Size:</b>	350g Aerosol
<b>Finish:</b>	Matt
<b>Colour:</b>	8 Standard and 6 Fluoro colours
<b>Consistency:</b>	Liquid
<b>Coverage:</b>	Will <b>COVER 4-6 m<sup>2</sup></b> or produce 200 'X' marks, 80-100m in a 50mm continuous line.
<b>Clean Up:</b>	Acetone or General Purpose Thinner

## STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. (Do not store in vehicles under hot conditions). Store in a well ventilated place.

## DISPOSAL

Pressurised container: Do not pierce or burn, even after use. Aerosol should be completely emptied prior to disposal. Dispose of contents/container according to regional regulations.

## FIRST AID/SAFETY INFORMATION

**Please refer to Safety Data Sheet before use.** Safety data sheets are available for download from our website:

[www.tradegear.co.nz](http://www.tradegear.co.nz)

**Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766** or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

**Keep out of reach of children.**

## DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Tradegear; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Tradegear recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact Tradegear on 0800 22 44 34.