

# CLEAN BRAKE

## Heavy Duty Cleaner

Date: 4 May 2016

### YOUR SMART ADVANTAGES

- Excellent degreaser
- Leaves no residue
- Non-staining and non-corrosive
- Balanced evaporation rate for optimum cleaning and shortest dry time
- CFC Free
- Made in New Zealand

### USES

- Cleaning disc brakes to prevent brake noise caused by contamination or stop clutch slipping.
- General purpose degreaser for automotive workshops.
- Cleaner and degreaser for tools and equipment.
- Suitable for mechanical and industrial cleaning and degreasing operations.

### PRODUCT CHARACTERISTICS

Colour Colourless

Product codes

500ml Aerosol	30607922
20L Metal drum	30607293

### DIRECTIONS FOR USE

Read the Safety Data Sheet before commencing work. Work in a well ventilated area, out of direct sunlight. Avoid contact with skin - wear solvent resistance gloves. Check compatibility with rubber and plastic components that may come into contact with Clean Brake. Mask delicate substrates if necessary.

### APPLICATION

#### AEROSOL

- Ensure part to be cleaned has cooled to room temperature.
- Shake the can well before use.
- Place a suitable collection container under the part to be cleaned.

- Starting at the top and spray liberally, washing the residues down and off into the collection container.
- Allow excess to run off.
- Dry with a clean absorbent cloth using the wipe on, wipe off technique, or leave to air dry.
- Ensure all cloths, paper towels and other absorbent surfaces are properly dried or immersed in water to soak overnight before discarding.
- Badly soiled areas may require more than one application.

#### 20L DRUM

- Ensure part to be cleaned has cooled to room temperature.
- Decant Clean Brake into a suitable, clean container.
- Small parts may be fully immersed into the container and cleaned using a paintbrush.
- Remove cleaned item and allow to drain.
- Larger parts may be placed on absorbent towels and cleaned using a paintbrush dipped into the brake cleaner.
- Allow excess to run off.
- Dry with a clean absorbent cloth using the wipe on, wipe off technique, or leave to air dry.
- Ensure all cloths, paper towels and other absorbent surfaces are properly dried or immersed in water to soak overnight before discarding.

### LIMITATIONS

- Avoid contact with decorative and automotive finishes. These may be damaged if in contact with Clean Brake.
- At very low temperatures cold cans will not spray with high pressure.

### STORAGE AND SHELF LIFE

Store between 5 and 25°C, ventilate if above 25°C. Do not store above 35°C. Do not leave in trunk of car, inside car or anywhere in full sunlight or high temperatures, due to the high risk of bursting the can. Do not expose to temperatures exceeding 50°C.

Shelf life is a minimum of 2 years if stored as directed.

## BOSTIK CLEAN BRAKE

### DISPOSAL

Do not puncture or burn cans even when empty. Empty containers may be disposed via local landfill.

Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

### PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit [www.bostik.co.nz](http://www.bostik.co.nz) for copies.

HIGHLY FLAMMABLE –KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME

HARMFUL IF INHALED

KEEP OUT OF REACH OF CHILDREN

### FIRST AID

Call a POISON CENTER or doctor/physician if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Give water to rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician

**For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMCALL, phone 0800 243 622.**

BOSTIK HOTLINE

Smart help 0508 222 777



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.co.nz](http://www.bostik.co.nz)

Technical Advice

Tel: 0508 222 777

[nzsales@bostik.com](mailto:nzsales@bostik.com)