

# WKCP-D (SQ Ceramic)

Flange head construction screw with TX drive

Diameters:  $\varnothing 5$  mm |  $\varnothing 6$  mm |  $\varnothing 8$  mm |  $\varnothing 10$  mm

Length range: from 40 to 600 mm



Flange head construction screw with TX drive for structural connections of wooden members, including solid, bonded and wood-based panels.



TX DRIVE



HIGH CORROSION RESISTANCE  
C4 COATING



EUROPEAN TECHNICAL  
ASSESSMENT  
ETA-18/0817

SCREW MATERIAL - Carbon steel

ANTI-CORROSION PROTECTION - SQ Ceramic (C4 Coating)

## PRODUCT ADVANTAGES:



**FLANGE HEAD** - Flange head increases the bearing area and provides tight connection as well as resistance to prevent head pull-through.




**SHANK RIBS** - Shank ribs reduce installation torque by reaming the hole.



**HIGH TORQUE** - Allows screws to be installed without pre-drilling, even in hardwood substrates.



**WAX COATING** - Wax coating applied during the production process significantly reduces the torque.



### NEW CUTTING EDGE / SERRATED THREAD

New special design of cutting edge with added milling reduces screwing resistance by 20%. This helps to extend the life of batteries and power tools. Special cutting notches integrated on the thread cut wood fibres structure while screwing in.

### DOUBLE THREAD

Additional recessed second thread improves remarkably the speed of timber penetration and reaction time of first grip into the wood.


EXAMPLES OF APPLICATIONS:



SUBSTRATES



Solid timber



Glued laminated timber  
CLT, KVH, BSH/GLT



Laminated Veneer  
Lumber - LVL

INSTALLATION INSTRUCTIONS (screw requires no pre-drilling)

